

PAVEMENT SAVIOUR

SLURRY SEAL FOR PAVEMENT REPAIR

Features

- Minimize oxidation / ageing
- Reduce water infiltration
- Provide skid resistance
- Improve aesthetic
- Correct raveling and weathering
- Non-toxic, cold applied and safe to use

Preparation before construction

- Power blow or sweep pavement surface
- Medium and large cracks filled
- Add 20% water by weight to mix
- Stirring evenly with a stirrer which speed above 200 RPM
- Use hand squeegee flattened to less than 3 mm

Application condition

- Temperature : Above 10°C (50°F)
- Wind : Slight breeze beneficial
- Sunlight : Necessary
- Do not work : If rain is imminent or freezing anticipated within 24 hours.

Color : **Green**, **Black**, **Grey**, **Red**

Package : 25 kg/barrel

Storage : Store in a place with moisture



Rigid Pavement



Flexible Pavement



HPB TECHNOLOGY CO., LTD.

3F, No. 199-3, Sec. 3, Chung Hsiao E. Rd., Taipei City 106, Taiwan

Tel : **+886-2-2752-6181** Fax : **+886-2-2752-6096**

Email : hpb.tech@msa.hinet.net Website : www.hpb.com.tw

www.hpb.com.tw